



AMENDMENTS TO THE CLAIMS

This listing of claims replaces all prior versions and listings of claims in the application:

RECEIVED

JUN 2 2 2004

Listing of Claims:

Technology Center 2600

1 (currently amended). A device that calculates a white balance control amount for an electronic still camera, comprising:

an image signal generator that generates an image signal corresponding to a first image formed on a light receiving surface of an imaging device;

an image area extractor that extracts at least one image area, which contains a second image of a subject positioned at a predetermined distance from said electronic still camera, from said first image; and

a control amount calculator that calculates a control amount for performing a white balance adjustment, based on an image signal relating to a single image area contained in said at least one image area, wherein said image area extractor comprises a three dimensional image data sensing processor that senses three dimensional data indicating a distance from

said electronic still camera to each point on a surface of said subject to obtain said second image.

2 (previously presented). The device of claim 1, wherein said image area extractor extracts said single image area, and said control amount calculator calculates said control amount, based on said image signal relating to said single image area which is extracted by said image area extractor.

3 (previously presented). The device of claim 2, wherein said second image is in-focus, and said single image area is extracted by selecting pixels from said first image, said pixel corresponding to points within a predetermined range from said predetermined distance.

4 and 5 (canceled).

6 (previously presented). The device of claim 1, wherein said control amount calculator extracts a third image composed of an achromatic color from said second image of said image area extracted by said image area extracting processor, and calculates said control amount based on only said third image.

7 (canceled).

8 (previously presented). The device of claim [[7]] 1, wherein said three dimensional image data sensing processor comprises a light source radiating a distance measuring light beam onto said subject, and a three dimensional image signal generator that generates three dimensional data indicating a distance from said electronic still camera to each point on a surface of said subject.

9 (currently amended). The device of claim 8, wherein said three dimensional image signal generator comprises said image signal ~~generating processor~~ generator.

10 (previously presented). The device of claim 8, wherein said three dimensional image signal generator comprises:

a plurality of photoelectric conversion elements that receive a reflected light beam from said subject, so that a signal charge corresponding to an amount of said received reflected light beam is accumulated in each of said photoelectric conversion elements;

a signal charge holder disposed adjacent to each of said photoelectric conversion elements;

an electric charge discharger that discharges an unwanted charge accumulated in each of said photoelectric conversion elements, so that said accumulation of said signal charge is started in each of said photoelectric conversion elements;

a signal charge transferor that transfers said accumulated signal charge in said photoelectric conversion elements to said signal charge ~~holding unit~~ holder; and

a signal charge integrator that alternately drives said electric charge discharger and said signal charge transferor, so that said signal charge is integrated in said signal charge holder.

11 (currently amended). A device that calculates a white balance control amount for an electronic still camera which photographs an image containing at least one subject and at least one portion other than said at least one subject, said white balance control amount calculating device comprising:

an ~~[[an]]~~ imager by which an image signal corresponding to said image is generated;

an image area extractor that extracts at least one image area, each image area containing one of said at least one subject, from said image; and

a control amount calculator that calculates a control amount for performing a white balance adjustment, based on said image signal relating to a single image area contained in said at least one image area, wherein said image area extractor comprises a three dimensional

PI9364.A05

image data sensing processor that senses three dimensional data indicating a distance from said electronic still camera to each point on a surface of said subject to obtain said at least one image area.